Turkish Online Journal of Qualitative Inquiry (TOJQI) Volume 12, Issue 7, July, 2021:1820 – 1827

Vibrational Behavior Of Kevlar Epoxy Composite Fibre

K.S. Sathishkumar¹, S.Ramesh Kumar², A.Jeevarathinam³, Ganesh Kumar. K. V⁴, Dr.S.Kalpana⁵,

Abstract

In this study, the Taguchi technique was used to investigate the impact and optimization of machining parameters on vibration in turning operations. Experiments were carried out with varying cutting speeds, victual rates, and cutting depths. In this analysis, two distinct Kevlar materials with the same ratio as Shim are used. An orthogonal array, the signal-to-noise (S/N) ratio, and analysis of variance (ANOVA) were used to investigate performance characteristics in the turning of oil-hardened non-shrinking steel using SNMG 120408 EN - TMR insert cutting implements.

Keywords: OHNS, Turning parameters, Taguchi, Shim, Vibration, Surface finish, S/N ratio.

1.Introduction

Vibration in computers has piqued the interest of many people for many years. It has formulated a crucial design characteristic in many situations, such as components subject to fatigue loads, precision fits, fastener apertures, and aesthetic requirements. One of the most critical constraints for the culling of machines and cutting parameters in process orchestration in the integration of tolerances is vibration in implements. As a result of vibrations, a large number of experiments have been conducted to investigate the general effects of celerity, victual, and cut depth in computer implements. Process simulation and optimization are the two most difficult challenges in the processing of goods. Process variables that interact define the output processes. Nowadays, more

¹Associate Professor, Department of Mechanical Engineering, Rathinam Technical Campus, Tamilnadu,641021, INDIA.

²Department of Mechanical Engineering, Rathinam Tehnical Campus, Tamilnadu, 641021, INDIA.

³Assistant Professor, Department of Mechanical Engineering, Hindusthan Institute of Technology, Tamilnadu, 641021, INDIA.

⁴AssistantProfessor, Department ofMechanical Engineering, Hindusthan Institute of Technology, Tamilnadu, 641021,INDIA.

⁵Professor, Department of Commerce, PSG College of Arts and Science, Tamilnadu, 641014, INDIA. *Correspondence: erkssathishkumar@gmail.com,

emphasis is placed on the industry's accuracy and the surface roughness of the substance. Surface finishing was one of the most important factors in determining the system installation of components. In this regard, an attempt was made to calculate the damping coefficient based on experimental results. Using the Taguchi process, an attempt was made to refine the damping coefficient presage model. Because turning is the primary procedure in the majority of the industry's engendering methods, the surface finish of turned components has a greater influence on product consistency. A number of variables, including haste, victual, and cutting depth, have been found to have varying effects on surface finish in turning. To gain a better understanding of the turning mechanism, it is necessary to consider not only the influence of each variable, but also the relationships between them. It is difficult to identify all of the variables that cause vibration in turning operations. Furthermore, determining the effect of each element on the output is costly and time consuming. To simplify the problem, categorical variables corresponding to practical applications must be reduced or eliminated. The Taguchi method entails orchestrating experiments with the goal of acquiring data in a controlled manner, carrying out these experiments, and analysing data to gain insight into the behaviour of a given process. It describes the experimental plans using orthogonal arrays, and the analysis of variance (ANOVA) is based on the treatment of the experimental outcomes.

2. Problem Definition

- The rate of cutting one of the cutting conditions that affects the surface roughness, it also leads to implement wear and unsuitable cutting conditions that result in burr on the work piece As a result, the standard cutting celerity should be culled. Edge damages such as flank wear, rake face wear, notching, and thermal thermal crack occur when high cutting celerity is culled.
- The rate of cutting One of the cutting conditions that affects surface roughness; it also leads to implement wear and unsuitable cutting conditions, which leads to burr on the work piece. As a result, the standard cutting haste should be eliminated. It also causes vibration on the implement, resulting in implement wear.

3.Fabrication selection

Following are the parameters considered while selecting the fabric.

- Strength (tensile, bending)
- Resistance corrosion
- Thermal properties
- Cost
- Thickness

The incorporation of a fabric layer into a resin matrix produces one material whose properties cannot be predicted by summarising the properties of its components in fabric-reinforced composite design stability. Although it is the combination of matrix, fabric, and manufacturing process that gives composites their superior performance, it is important to consider these components separately. When the above parameters are considered, the compositions culled are as

shown in the table. SHIM, A. The shim functions as both an insert and an operating shock absorber. As a result, the shim is used for dampers. Damping components, such as composites, were made of Kevlar fibre reinforced composite epoxy, and materials for the commercially available hardener K-6 were used. The dampers are kept between the implement holder and the insert.

4. Manufacturing of the Composites

The glass/Kevlar fibre reinforced epoxy composite incorporate was yare at various concentrations. The weight percentage of cotton, epoxy, was tenacious when density, categorical gravity, and mass were all considered. Compression moulding is used to process the composites at room temperature.

5. Compression molding method of preparation of test specimen

Compression moulding is one of the plastic industry's oldest manufacturing processes. The recent development of high vigour, expeditious remedies, sheet moulding compounds, bulk moulding compounds, and advancements in press technology are making compression moulding a very common method for mass production of composite products. Fully assembled parts are moulded in matched metal compression moulds that provide the final component form. The ability of compression moulding to produce components with involute geometry in short periods of time is its primary advantage. Typically, the mould temperature ranges from 130°C to 160°C (270°F to 320°F).



Figure 1. Compression Molding Machine

6. Specimen Preparation

The prepared slabs of the composite materials were taken from the mould for various mechanical tests according to ASTM specifications, and then specimens were yarned from composite slabs. The research samples were laminated using various instruments in the workshop. Three similar research specimens were YARs for separate studies. The specimens were cut into the form shims required for the application.



Figure 2. Shim

7. Methodology

Based on a review of the literature and previous experimental studies, a technique was developed to investigate the evolution of flank wear of cutting instruments and the transformation in the surface finish of the machined part during turning. Given that high-speed dry machining is the latest manufacturing trend, it was proposed to use dry machining and high turning speed to mimic the machining conditions that are visually studied in traditional manufacturing industries. This chapter describes the steps taken to achieve the objectives of this analysis. Manufacturers of cutting implements authoritatively mandated commercially available cutting implements used by many manufacturing industries, and the happy machining parameter was culled in order to replicate the conditions in the manufacturing industry in the machining experiment. Cutting experiments were carried out on a traditional lathe system in dry conditions. The experiment was all set up on the KIRLOSKAR Turning Master-35 style lathe machine. The implements were put through their paces at 600 RPM, 700 RPM, and 800 RPM spindle speeds. The success rates used were 0.05 mm/rev, 0.07 mm/rev, and 0.09 mm/rev, which were kept constant across all cutting rates. This increased feed rate was used for maximum efficiency. In addition, cutting depths of 0.4mm, 0.6mm, and 0.8mm were used. The cutting conditions were kept constant for each of the shims used in the experiment.

Table 1. Operating Parameters				
Sl.No.	Cutting speed (m/min)	Feed rate (mm/rev)	Depth of cut (mm)	
1	· ,	0.07	0.4	
1	600	0.05	0.4	
2	700	0.07	0.6	
3	800	0.09	0.8	

Table 1. Operating Parameters

8. Experimental Procedure

The experiment includes determining the effect of two or more variables. For this type of experiment, fractional designs are generally the most effective. Using a fractional design, we discovered that in each complete trail or replication of the experiment, all possible coalescences of the calibres of the factors are investigated. For example, if a' level factor A and 'b' level factor B exist, all 'ab' treatment amalgamations are included in each replicate. When variables are arranged to be crossed in a factorial design, they are frequently expressed verbally. The effect of a factor is known as vicissitude in replication generated by a transmutation in the factor calibre.

This is often referred to as a primary effect because it is related to the primary variables of interest in the experiment. Three parameters were collected for analysis in this study: celerity, victual, and cutting depth. Several tribulation runs were carried out to determine the parameter range. For the parameters, the calibres were definitively extracted from table 1.

8.1 Hard Turning

Hard turning is a cutting method defined by suitable cutting tools and high cutting speed, as well as turning materials with a hardness greater than 45 HRC. Hard steel machining with advanced tool materials, such as mixed ceramic, has more advantages than grinding or polishing without the use of cutting fluid, such as a shorter cycle time, process flexibility, compatible surface roughness, a higher rate of material removal, and fewer environmental issues. High-speed machining of dies and moulds in their hardened state has become standard industry practise due to increased productivity and reduced energy consumption.

Hard turning is a cost-effective, high-efficiency, and flexible machining process for ferrous metal workpieces that are frequently hardened above 40 HRC and up to 62 HRC. This process is now widely used in the production of gears, shafts, bearings, cams, forgings, dies, and moulds. Because of the required tool material hardness, hard machining is done dry with ceramics and polycrystalline cubic boron nitride (PCBN, also known as CBN) cutting tools. Hard turning is a lathe machining method in which most of the cutting is done with the nose of the inserts, in addition to the effects of work material hardness, tool geometry, and cutting conditions on the surface integrity of the finished parts. Because hard turning necessitates the use of a strong and prudent cutting-edge tool, it is critical to provide high edge strength as well as favourable surface roughness in the nose design through proper edge preparation. The efficiency and quality of machined surfaces of ceramic and CBN cutting tools are strongly dependent on cutting conditions, such as cutting speed, feed, cutting depth, and nose radius of the tool, all of which have a significant impact on surface finish due to vibration in the turning tool. In this experiment, the working component is OHNS steel. The OHNS steel has a diameter of 50mm and a weight of 350mm. The chemical composition and mechanical properties of OHNS steel are shown in tables 2 and 3.

Table 2. C	Chemical co	omposition	of OHNS	steel
------------	-------------	------------	---------	-------

С	Mn	Cr	W
0.85%	1.00%	0.50%	0.265%

14010 51	1,100mail	ear proper	nes or orn	
Max	Yield	Proof	Impact	Hardness
stress	stress	stress	strength	value
950	465	480	25j	288
N/mm	N/mm	N/mm	5	Brinell

Table 4	Observations	recorded for	damning	coefficient
1 auto +.	Observations	ICCOILICU IOI	uamping	coefficient

SI No	Damping coefficient	Damping coefficient	Damping coefficient
5110	for	for	for Kevlar

K.S. Sathishkumar, S.Ramesh Kumar, A.Jeevarathinam, G	Ganesh Kumar. K. V, Dr.S.Kalpana	ι,
---	----------------------------------	----

	cemented	chopped Kevlar	mat
	carbide		40wt%
	shim	40wt%	
1	0.01325	0.034	0.1275
2	0.042	0.104	0.1
3	0.023	0.15	0.225
4	0.089	0.035	0.06
5	0.0178	0.09	0.24
6	0.058	0.047	0.056
7	0.0212	0.08	0.056
8	0.022	0.028	0.029
9	0.102	0.25	0.15

 Table 5. Comparison of S/N ratio

 Sl. S/N ratio for S/N ratio

SI.	S/N ratio for	S/N ratio	S/N ratio
			for Kevlar
No	Cemented	for Chopped	Mat
	Carbide	Kevlar	40wt%
	Shim	40wt%	
1	37.55	29.37	17.88
2	27.53	19.65	20
3	32.76	16.47	12.95
4	21.01	29.11	24.43
5	34.99	20.91	12.39
6	24.73	26.55	25.03
7	33.47	21.93	25.03
8	33.15	31.05	30.75
9	19.82	12.04	16.47




Fig 4. Comparison of S/N ratio value for all specimens

9.Conclusion

The Taguchi method was carried out with the help of Minitab software. The Taguchi methods are used to look at the value of the damping coefficient and the SN ratio for the experimental variables of factors. These strategies are frequently used to improve replications. ANOVA (analysis of variance) is calculated and tabulated for the proposed method. In addition, the design's regression equation was discovered. Because surface quality will be high when the S/N ratio values are miniscule, the more minute phenomenon is eliminated for damping coefficient. In this experiment, two kevlar versions in the same ratio were chosen and used as shims. As a shim, chopped Kevlar of 40% weight and Kevlar mat of 40% weight were used. The damping coefficients of various Kevlar versions that are used as shims are calculated and compared. By comparing the S/N ratio values of the two different Kevlar materials, it has been shown that the Kevlar Mat of 40% weight is more suitable for dry machining OHNS steel, resulting in a superior surface finish.

10.References

- [1]H.K. Tönshoff, C. Arendt, Amor R. Ben, Cutting of hardened steel, CIRP Annals 49/2 (2000) 547-566.
- [2]G. Byrne, D. Dornfeld, B. Denkena, Advancing cutting technology, CIRP Annals 52/2 (2003) 483-507.
- [3]W. König, A. Berktold, K.F. Koch, Turning versus grinding-a comparison of surface integrity aspects and attainable accuracies, CIRP Annals 42/1 (1993) 39-43.
- [4] F. Klocke and E. Brinksmeier, et al, Capability profile of hard cutting and grinding processes, CIRP Annals 54/2, 2005, 557-580.
- [5]Merdol, S. D. & Altintas, Y, Mechanics and dynamics of serrated cylindrical and tapered end mills. Trans. ASME.
- [6] Tlusty, J. Machine Dynamics, Handbook of High Speed Machining Technology. King, R.I., ed., 1985, Chapman and Hall, New York.

- [7]Altintas, Y. and Budak, E. Analytical prediction of stability lobes in milling. Ann. CIRP, 44(1), 1995, 357-362.
- [8]Tlusty, J. Machine Dynamics. Handbook of High Speed milling, J. of Engineering for Industry, Trans.ASME, 108, May 1986, 59-67.
- [9]Smith, S. and Tlusty, J. Update on high-speed milling dynamics. J. Engineering for Industry, Trans. ASME, 112, May 1990, 142-149.
- [10] Jaganathan, V. A study of the dynamics of drilling and reaming. Ph.D. Thesis, Univ. of Windsor, Canada, 1998.
- [11] Tian, J. Self-excited vibration of rotating discs and shafts With applications to sawing and milling. Ph.D. dissertation, The Univ. of British Columbia, Canada, August 1998. Proceedings of the 2006 IJME – INTERTECH Conference
- [12] Fofana, M. S., Delay dynamical systems with applications to machine- tool chatter. Ph.D. Thesis, Univ. of Waterloo, Canada, 1993.
- [13] Merritt, H.E. Theory of self –exited machine tool chatter-Contribution to machine tool chatter research –1, ASME J Eng for Ind., 87, November 1965, 44-454
- [14] Dohner, J. L., et al. Mitigation of chatter instabilities in milling by active structural control. J. Sound & Vibration, 269, 2004, 197-211.
- [15] Tobias, S.A. and Fishwick, W, Theory of regenerative machine tool chatter, The Engineer, London, Vol.205, 1958, 199-203 (Feb7), 238-239 (Feb, 14),
- [16] Choi, T. and Shin, Y., Online chatter detection using wavelet based parameter estimation, Feb. 2003, J.Manufacturing Science & Engineering, 125, 21-28.
- [17] Amin, A. and Abdelgadir, M. The effect of preheating of work material on chatter during end milling of medium carbon steel performed on a vertical, machining center, Nov. 2003, J. Manufacturing Science & Engineering, 125, 674-680.
- [18] Faassen, R. P. H, and van de Wouw, et.al, Prediction of regenerative chatter by modeling and analysis of high-speed milling. , 2003, Int. J. Mach. Tools Manuf., 43, 1437-1446.
- [19] Koenisberger and Tlusty J, Machine tool structures, 1967, vol. I: stability against chatter. Pergamon, Englewood Cliffs
- [20] Cao HG and Holkup T, et.al, A comparative study on the dynamics of high speed spindles with respect to different preload mechanisms., 2011, Int J AdvManufTechnol 57:871–883
- [21] Hung JP and Lai YL, et.al, 2011, Modeling the machining stability of vertical milling machine under the influence of the preloaded linear guide. Int J Mach Tools Manuf 51(9):731–739
- [22] Kolar P, Sulitka M, 2011 Simulation of dynamic properties of a spindle and tool system coupled with a machine tool frame. Int J AdvManuf Techno 54:11–20.
- [23] Albertelli P, Cau N, Bianchi G, Monno M (2012) The effects of dynamic interaction between machine tool subsystems on cutting process stability. Int J AdvManuf Techno 58:923–932